

MULTI SIZE HIGH PRESSURE PIPE PLUGS



They are used to seal the pipe in which the back pressure exceeds the working pressure range of standard plugs.

With these plugs is guaranteed the reliability and safe operation at high pressures due to the special reinforced covering in aramid from the top the bottom.

The plugs are equipped with eyelets bolts and quick couplings for inflation and deflation.

Part Number	Nominal Size	Min. Pipe Diameter	Max. Pipe Diameter	Max. Working Pressure	Back pressure	Product Diameter	Product Total Length	Product Weight
		[mm]	[mm]	[bar]	[bar]	[mm]	[mm]	[kg]
HPAB100	100	100	100	12	6	88	550	1,0
HPAB100150	100-150	100	150	6	3	88	550	1,0
HPAB150	150	150	150	12	6	138	550	1,2
HPAB150200	150-200	150	200	6	3	138	550	1,2
HPAB200	200	200	200	12	6	185	650	3,4
HPAB200300	200-300	200	300	6	3	185	650	3,4
HPAB300	300	300	300	12	6	285	850	6,6
HPAB300400	300-400	300	400	6	3	285	850	6,6
HPAB375	375	375	375	12	6	380	1000	9,4
HPAB375500	375-500	375	500	6	3	380	1000	9,4
HPAB500	500	500	500	12	6	485	1150	23,0
HPAB500600	500-600	500	600	6	3	485	1150	23,0
HPAB600	600	600	600	12	6	585	1300	25,5
HPAB600700	600-700	600	700	6	3	585	1300	25,5
HPAB800	800	800	800	12	6	785	1300	40,0
HPAB8001000	800-1000	800	1000	6	3	785	1300	40,0