



GÖKSU INFRASTRUCTURE EQUIPMENTS AND CONSTRUCTION LTD.CO



MULTI SIZE FLEXIBLE PIPE TEST PLUGS 1,5 BAR

The plugs can be easily installed at any angle throughout the pipe, which allows having an effective sealing. These plugs are mainly used for testing of sealing with air or water.

Environmentally resistant, to temperature from -40 to 70⁰ C. Standard series of test plugs can be made in a range of diameters from 50 to 3600 mm.

Part Number	Nominal Size	Min. Pipe Diameter	Max. Pipe Diameter	Max. Working Pressure	Product Diameter	Product Total Length	Bypass Diameter	Product Weight
		(mm)	(mm)	(bar)	(mm)	(mm)	(inch)	(kg)
HPAPB5060	50	50	60	6,0	45	330	1/8"	1,0
HPAPB50	50	50	50	12	45	330	1/8"	1,0
APB701501	70-150	70	150	1.5	64	400	½ "	1.2
APB1002001	100-200	100	200	1.5	88	500	1"	1,8
APB1503001	150-300	150	300	1.5	138	580	2"	4.0
APB2004001	200-400	200	400	1.5	185	680	2"	7,2
APB3006001	300-600	300	600	1.5	285	850	2"	11,0
APB3757501	375-750	375	750	1.5	360	1000	2"	18,0
APB3757502	375-750	375	750	1.5	360	1000	2"+1"	20,0
APB50010001	500-1000	500	1000	1.5	485	1200	2"	27,0
APB60012001	600-1200	600	1200	1.5	585	1400	2"	35,0
APB80012001	800-1200	800	1200	1,5	780	1200	2'	35,0