



GÖKSU INFRASTRUCTURE EQUIPMENTS AND CONSTRUCTION LTD.CO

SMALL PIPE TEST PLUGS WITH BYPASS

These test plugs are mainly used for sealing sewer connections. They are used in the test system and pipeline leak. The plugs are made with high quality rubber, and metal items for anticorrosion.

Standard type series are manufactured in diameters from 30 to 650 mm. They are used for testing of sealing by air, water and by-pass. Resistant to the environment, to temperatures from -40 to 70⁰ C



Part Number	Nominal Size	Min. Pipe Diameter (mm)	Max. Pipe Diameter (mm)	Max. Working Pressure (bar)	Product Diameter (mm)	Product rubber Length (mm)	Diameter Bypass (inch)	Product Weight (kg)
APE30	1 ¼"	30	32	2.5	29	30	1/8"	0.14
APE40	1 ½"	38	42	2.5	37	40	1/8"	0.15
APBE50	2"	48	54	2.5	45	50	1/8"	0.25
APBE60	2 ½"	59	65	2.5	58	90	½"	0.35
APBE75	3"	72	78	2.5	69	110	½"	0.45
APBE100	4"	90	105	2.5	88	150	½"	0.6
APBE150	6"	150	150	2.5	138	150	2"	1.5
APBE200	8"	200	200	2.5	180	200	2"	2
APBE250	10"	250	250	2.5	225	250	2"	2.5
APBE300	12"	300	300	2.5	285	300	2"	3.2
APBE400	16"	400	400	2.5	380	450	2"	4.2
APBE500	20"	500	500	2.5	480	450	2"	5.4
APBE600	24"	600	600	2.5	580	450	2"	6.5
APBE800	32"	800	800	2,5	780	800	2"	30.0

Part Number	Nominal Size	Min. Pipe Diameter	Max. Pipe Diameter	Max. Working Pressure	Product Diameter	Product rubber Length	Diameter Bypass	Product Weight
APBE3040	1 ¼"-1 ½"	30	40	2,5	29	30	1/8"	0,5
APBE5075	2"-3"	48	75	2.5	48	80	½"	0.75
APBE70100	3"-4"	88	105	2.5	88	150	1"	2.5
APBE100150	4"-6"	90	150	2.5	88	150	½"	0.75
APBE150200	6"-8"	150	200	2.5	138	200	2"	2.5
APBE200250	8"-10"	200	250	2.5	180	250	2"	4
APBE250300	10"-12"	250	300	2.5	225	300	2"	6
APBE300350	12"-14"	300	350	2.5	285	300	2"	8.5
APBE400450	16"-18"	400	450	2.5	380	450	2"	4.2
APBE500550	20"-22"	500	550	2.5	480	450	2"	5.4
APBE600650	24"-26"	600	650	2.5	480	450	2"	6.5
APBE8001000	32"-40"	800	1000	2,5	780	800	2"	35.0