



GÖKSU INFRASTRUCTURE EQUIPMENTS AND CONSTRUCTION LTD.CO

ZİNC PLATED STEEL TEST PLUG

The plugs are used to block sewer pipes, to repair and weld, to make hydro testing and pipe welding in an inert tube. The plugs are easy to install and temperatures until 100 ° C. They are available in the bypass. Sturdy and lasting with a oil resistant NBR gasket.



Part Number	Nominal Size	Min. Pipe Diameter (mm)	Max. Pipe Diameter (mm)	Max back pressure (bar)	Bypass Diameter (inch)
ZPSTP40	1 ½"	36	50	2	1/2"
ZPSTP50	2"	50	60	2	1/2"
ZPSTP65	2 ½"	60	75	2	½"
ZPSTP75	3"	70	85	1,2	½"
ZPSTP90	3 ½"	85	100	1	½"
ZPSTP100	4"	95	105	0,6	½"
ZPSTP115	4 ½"	110	125	0,6	½"
ZPSTP125	5"	120	140	0,6	½"
ZPSTP150	6"	145	160	0,5	½"
ZPSTP175	7"	175	200	0,4	½"
ZPSTP200	8"	195	215	0,4	½"
ZPSTP225	9"	210	230	0,4	½"
ZPSTP250	10"	245	260	0,4	½"
ZPSTP300	12"	296	320	0,3	½"
ZPSTP350	14"	340	385	0,3	½"
ZPSTP375	15"	370	415	0,3	½"
ZPSTP400	16"	390	430	0,3	½"
ZPSTP450	18"	448	495	0,3	½"
ZPSTP500	20"	495	558	0,2	½"

Double seal plugs can be supplied to order.