



GÖKSU INFRASTRUCTURE EQUIPMENTS AND CONSTRUCTION LTD.CO

MULTI SIZE FLEXIBLE PACKER WITH BYPASS AND WHEELS



Flexible packers have a single ply of rubber textile covering and at every corner both have wheels placed at an angle of 120 °. These rollers provide stability in movement inside the pipe. The design of these packers allows water flow during the repairing process. The area of length is from 600 to 5000 mm.

These flexible packers can be easily installed in the pipeline.

Part Number	Nominal Size	Cylinder Length	Max. Contact	Required Inflation Pressure	Product Diameter	Product Total Length	Bypass Diameter	Product Weight
		(mm)	(mm)	(bar)	(mm)	(mm)	(inch)	(kg/m)
FRP100150XX	100-150	1000-5000	S.U-170	2.5	60	S.U+350	NA	1.7
FRP150250XX	150-250	1000-5000	S.U-225	2	116	S.U+350	2"	3.3
FRP200300XX	200-300	1000-5000	S.U-280	2	150	S.U+350	2"	5.4
FRP300400XX	300-400	1000-5000	S.U-300	1.5	231	S.U+350	4/3'	7.3
FRP400600XX	400-600	1000-5000	S.U-300	1	345	S.U+350	4/3'	11.6
FRP600800XX	600-800	1000-5000	S.U-300	1	444	S.U+350	4/3'	15,5