



GÖKSU INFRASTRUCTURE EQUIPMENTS AND CONSTRUCTION LTD.CO

LIFTING BAGS

These pillows are made with high quality rubber. The lifting bags allow moving heavy



objects during natural disasters, to release people in the road and rail accidents, to make installation of heavy machinery. It also helps with installation, and remote maintenance of all types of pipelines, used for cracking and removal of stone blocks. Can be widely applied on the ground and used for processes in the army. For this product we have mining approval

Standard type series are available in 12 sizes with capacities from 1 to 76 tons.

Maximum working pressure: 8 bar [In order can be produce higher pressure and size](#)

Test Pressure: 12 bar

Brust Pressure > 32 bar

Thichness: 22 mm

These type of lifting bag can be produced with more or less workingpressure according to customer needs and we have mining approval

Part Number	Max. Lifting Thrust (t)	Max. Lifting Height (mm)	Wide (mm)	lenght Size (mm)	Weight (Kg)	Air Requiment (Lt)	Inflation Time (sec)	Handless
LB115	1.15	75	140	140	0,4	2,9	0,5	X
LB350	3.5	100	260	200	1,0	15,5	1,3	X
LB620	6.2	170	300	300	2,0	40,0	2,0	4
LB1030	10.3	210	380	380	3,8	85,0	5,0	4
LB1300	13	170	300	600	4,0	115,0	8,0	4
LB1840	18.4	290	500	500	6,4	198,0	12,0	4
LB2430	24.3	200	330	1000	9,1	215,0	12,0	4
LB2700	27	360	600	600	9,8	380,0	20,0	4
LB3700	37	420	700	700	13,5	630,0	30,0	4
LB4870	48.7	470	800	800	17,8	945,0	53,0	4
LB6200	62	500	900	900	21,0	1450,0	70,0	4
LB7600	76.8	590	1000	1000	24,5	1580,0	90,0	4